



Kingfisher

Direct Ltd

TX15150M

Electric Driven Pressure Washer



**15
Lpm**

**150
Bar**

**2175
Psi**

**415
Volts**

TX15150M



15
Lpm


150
Bar



TX range of electric cold water pressure washers offer an unsurpassed combination of styling and engineering excellence. Manufactured to the highest quality with unbeatable levels of reliability and durability.



**Optional
Hose Reel**



**Interpump
44 Series**

General	
Weight	43Kg
Dimensions	L860 - W400 - H875 mm
Noise level	LWA 93dB
Stop/Start	Manual Switch
Chemical injection	Low pressure system
Trolley	Thermoplastic, chemical tank & hose holder
Gun & lance	Two piece gun & lance assembly
Nozzle head	Variable angle with high-low pressure
HP hose	8m of 5/16" hose with 22mm couplings
Required water supply	20 Lpm
Max water inlet temp	60° C - 140° F

Pump	
Make	Interpump
Model	44 Series
Flow	15 Lpm
Pressure	150 Bar - 2175 Psi
Lubrication	Oil splash
Materials	Ceramic plungers brass manifold
Speed	2800 Rpm
Drive	Male shaft pump - Hollow shaft motor
Pressure control	Controlset with adjustable pressure
By-pass system	Internal recirculation

Electric Motor	
Power	415 Volts, 5kW, 50Hz, 8.5 Amps
Motor Protection	Thermal Protection to IPX5
Insulation	Class F
Power Cable	Length - 5m, Wire gauge - 2.5mm ² / 14AWG

Kingfisher Direct Ltd
 Retford Enterprise Centre
 Retford
 Nottinghamshire
 DN22 7GR
 01777 858009
 Company Reg No: 07752788
 VAT No: 120941249
 info@kingfisherdirect.co.uk