

## Kingfisher Direct Ltd

## **TX12100M**

**Electric Driven Pressure Washer** 



12 Lpm 100 Bar 1450 Psi 230 Volts

## **TX12100M**



**TX** range of electric cold water pressure washers offer an unsurpassed combination of styling and engineering excellence. Manufactured to the highest quality with unbeatable levels of reliability and durability.



Optional Hose Reel



Interpump 44 Series

General	
Weight	43Kg
Dimensions	L860 - W400 - H875 mm
Noise level	LWA 93dB
Stop/Start	Manual Switch
Chemical injection	Low pressure system
Trolley	Thermoplastic, chemical tank & hose holder
Gun & lance	Two piece gun & lance assembly
Nozzle head	Variable angle with high-low pressure
HP hose	8m of 5/16" hose with 22mm couplings
Required water supply	15 Lpm
Max water inlet temp	60° C - 140° F

Pump	
Make	Interpump
Model	44 Series
Flow	12 Lpm
Pressure	100 Bar - 1450 Psi
Lubrication	Oil splash
Materials	Ceramic plungers brass manifold
Speed	1450 Rpm
Drive	Male shaft pump - Hollow shaft motor
Pressure control	Controlset with adjustable pressure
By-pass system	Internal recirculation

Electric Motor	
Power	240 Volts, 3.2kW, 50Hz, 13.6 Amps
Motor Protection	Thermal Protection to IPX5
Insulation	Class F
Power Cable	Length - 5m, Wire gauge - 2.5mm <sup>2</sup> / 14AWG

Kingfisher Direct Ltd Retford Enterprise Centre Retford Nottinghamshire DN22 7GR 01777 858009

Company Reg No: 07752788 VAT No: 120941249 info@kingfisherdirect.co.uk