Product Assembly & Safe Use Instructions

Product: KDC Portable Store

This information sheet should be passed to the user/operator of this product before operation to ensure the product is used properly.



- 1. Ensure the store is assembled on level/flat ground for best results. This avoids bending of the chassis & complications with aligning the panel
- 2. Hand tighten nuts & bolts first to ensure correct alignment prior to tightening with the socket spanner.
- 3. Ensure minimum of 2 people carry out the assembly of this product.
- 4. Lift the product empty.



- 1. Attempt to assemble this product during high winds or adverse weather.
- 2. Walk over any of the panels during assembly as this might cause bending & deformation meaning that panels may not align correctly.
- 3. Stack this product after full assembly.
- 4. Lift the product unless it is completely empty & damage free.
- 5. Fully tighten components until completely aligned & fully located, this can cause damage and deformation if fully tightened prematurely.

All components & panels are galvanised and powder coated prior during the manufacturing process, however components should not be left outside longer



ALWAYS ensure that at least 2 people carry out the assembly of these stores. NEVER attempt to lift or move any of the panels without help to do so. Ensure hands are free from crushing prior to letting panels go.

Safetrade 247 operates a policy of continual improvement with regard to our products & services. Should you or your organisation have any comments/observations, which



Contents:

- 1. Floor panel x 1
- 2. Wall panels x 2
- 3. Rear panel x 1
- 4. Door panel x 1
- 5. Roof panel x 1,
- 6. Fixing & fastening, pack x 1
- 7. Lock cylinders x 2
- 8. Key sets x 3

Assembly Guide:



for the door.



Place the door panel (4) onto

the floor and secure using

bolts & washers by hand to

will hold the panel up.

the floor. Tip: An open door



Place the first wall panel (2) onto the floor & secure using bolts & washers by hand to the floor.



The wall panel (2) should be inter-locked with the door panel (4) at the corner then should be secured using bolts & washers by hand.



The store arrives flat-packed,



Position floor panel (1) in a


suitably prepared, level area

& ensure that the short end

is facing the correct direction







Lift the roof panel (5) and Lift and slide the roof panel rest against the door panel (5) onto the roof of the store, (4). Tip: This makes lifting ensuring the roof panel (5) locks into position all the the roof panel into position way around the sides & rear.



Secure the roof panel (5) to the side panels (2), rear panel (3) & door panel (4) using bolts & washers by hand. Tip: Move to align holes.

Place the rear panel (3) onto Repeat steps 4 & 5 which completes the last side of bolts & washers by hand to the store. Secure using bolts & washers by hand.



the floor & secure using

the floor.

Place both lock barrels into the holes locking with screw provided. Tip: Ensure the thumb lock is located inside the store.



Now that the store is assembled, using a socket spanner tighten all nuts and bolts that have been hand tightened only. Enjoy!