




Rubber Rib Mat

Rubber Rib Mat is a low cost, surface covering suitable for use in a wide variety of applications. The ribbed surface provides excellent grip for both floor surfaces and work areas alike. It is easy to cut and can be laid loose or glued/ fixed down for a more permanent solution. Available in two different thicknesses, 3mm and 6mm, Rubber Rib Mat is suitable for medium to heavy duty use.

Features

- ◆ **Typical applications:** Low-cost surface covering, suitable for industrial flooring, aisles, work benches, vehicle interiors, kennels, livery enclosures and animal grooming areas.
- ◆ **Material:** 100% rubber.
- ◆ **Cleaning:** Wash with cold water, use vacuum cleaner, or use pressure pump to remove dirt. The use of hard detergents is not recommended.
- ◆ **Sustainability:** REACH compliant. Contributes to a cleaner environment by reducing the need to use cleaning chemicals.
- ◆ **Warranty:** Lifetime.



Suitable for indoor and outdoor use



For more information about this product or, to place an order [click here](#)

Code	Metric	Imperial	Thickness	Weight	Type	Colour
RR391	90cm x 10m	3' x 33'	3mm	26.1kg	Roll	Black
RR691	90cm x 10m	3' x 33'	6mm	76kg	Roll	Black
RR6100	100cm x 10m	3' x 33'	6mm	83kg	Roll	Black
RR3122	120cm x 10m	4' x 33'	3mm	35kg	Roll	Black
RR6122	120cm x 10m	4' x 33'	6mm	97kg	Roll	Black
RR391C	90cm wide	3' wide	3mm	3kg	Cut length - per m	Black
RR691C	90cm wide	3' wide	6mm	7.6kg	Cut length - per m	Black
RR6100C	100cm wide	3' wide	6mm	8.3kg	Cut length - per m	Black

Our delivery promise

We guarantee your order will be shipped on time, every time. That's the Blue Diamond difference.

V4.11.23

Get in touch

+44 (0) 1779 841 899
sales@bluediamond.uk.com
www.bluediamond.uk.com

Rubber Rib Mat

Code	Metric	Imperial	Thickness	Weight	Type	Colour
RR3122C	120cm wide	4' wide	3mm	3.5kg	Cut length - per m	Black
RR6122C	120cm wide	4' wide	6mm	9.7kg	Cut length - per m	Black

Please note, the width and length can be +/- 2%

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number

Technical Specification

Slip resistant: Great slip resistance to level 2

Anti-fatigue: Good anti-fatigue properties, resistant to level 1

Wear resistant: Great wear resistance to level 2, suitable for medium to high footfall

Cut to length: Yes, mat can be cut to length

Cut to size: Yes, mat can be cut to bespoke sizes

Disability friendly: Yes, the low profile makes it suitable for wheelchair users

Dry area: Yes

Wheeled area: Yes, the low profile allows easy access for light weight wheeled traffic

Environment: Suitable for indoor and outdoor use

Impact resistant: Yes

Product testing:

- ◆ Hardness Shore A ± 5 65° ISO 7619-1
- ◆ SG (g/cm³) 1.50 ISO 2781
- ◆ Tensile (N/mm²) 2.5 ISO 37
- ◆ Elongation % 200 ISO 37

Sustainability:

- ◆ REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals)
- ◆ Contributes to a cleaner environment by reducing the need to use cleaning chemicals

Cleaning: Wash with cold water, use vacuum cleaner, or use pressure pump to remove dirt. The use of hard detergents is not recommended