

# Sychem Ltd

Process Heading	Product Specification
Reference	Alcohol-based hand gel
Created By	Sychem
Date	07/03/2020

TS Group, Unit 3, Mayflower Close, Southampton, SO53 4AR Tel: 0845 644 6824;

Email: <a href="mailto:sales@sychem.co.uk">sales@sychem.co.uk</a>

## **Safety Data Sheet**

# Sychem Alco Hand Sanitising Gel with Tea Tree Oil

SECTION1: IDENTIFICATION OF SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1 Product identifier

Product name	SYCHEM ALCO HAND SANITISING GEL WITH TEA TREE OIL		
Product number	SYC-AG5000-C, SYC-AG500-C-PT, SYC-AG5000-C, SYC-AG200-C, SYC-AG200-C-PT		

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Cleaning agent	
-----------------	----------------	--

### 1.3 Details of the supplier of the safety data sheet

Sychem Ltd, TS Group Unit 3,
Mayflower Close
Southampton
SO53 4AR
UK
Tel: 0845 644 6824
sales@sychem.co.uk

### 1.4 Emergency telephone number

Emergency telephone	Emergency contact number 0845 644 6824 (9am to 5pm Monday to Friday
	excluding bank holidays). Ask for Technical Department quoting the product
	name. Outside of these hours please contact your doctor or local hospital
	accident and emergency department or the NHS enquiry service (dial 111)
	quoting product name and present this MSDS advising them that the product is
	registered with the National Poisons Information Service



### **SECTION 2: Hazards Identification**

2.1 Classification of Substance or mixture

EYE IRRITANT 2 H319 Classification - EC 12722008

AQUATIC CHRONIC, 3 H412

**Physical Hazards** FLAMMABLE LIQUID 3-H226

**Health Hazards** EYE IRRITANT 2 - H319

**Environment Hazards** NOT CLASSIFIED

Classification – 67/548/EEC OR

1999/45/EC

**Human Health** 

Vapours and spray/mists in high concentrations are narcotic.

Symptoms following

R10

overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. Environmental The product is not expected to be hazardous to the environment. Physicochemical The product is flammable. Heating may generate flammable vapours.

### 2.2 Label Elements

### LABEL ELEMENTS

**Symbols** 





Signal word

**WARNING** 

Hazard statement

H226 Flammable liquid and vapour. H319 Causes serious eye irritation.

P102-KEEP OUT OF REACH OF CHILDREN.

**Precautionary Statement:** 

Prevention

P 15- RESTRICTED TO PROFESSIONAL USERS.

P233 Keep container tightly closed.

**Precautionary Statement:** 

Response

P370+P378 in case of fire: Use foam, carbon dioxide, dry powder or water

fog to extinguish.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/ container in accordance with national regulations. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor



Other Hazards	None
---------------	------

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2 Mixtures

Product	Percentage v/v	Cas No	EC No	REACH Reg No
De-ionised Water	27.9%			
Ethanol	>72% <76%	64-17-5	200-578-6 0	1-2119457610-43-XXXX
Methanol	>.5- <1%	67-56-1	200-659-6 0	-2119433307-44-XXXX
Glycerol	>.5% - <1.5%	56-81-5	200-289-5 E	xempt
Hydroxypropyl Methylcellulose	1%	7647-14-15	231-598-3 0	1-2119485491-33-XXXX
Tea Tree Oil	>.5% - <1.5%	68647-73-4	285-377-1	01-2120743651-57-XXXX

### SECTION 4 First aid measures

### 4.1 Description of First aid Measures

Inhalation	Place unconscious person on their side in the recovery position and ensure
	breathing can
	take place. When breathing is difficult, properly trained personnel may
	assist affected person
	by administering oxygen. Get medical attention if any discomfort continues.
	Remove any contact lenses and open eyelids wide apart. Continue to rinse
Eye contact	for at least 15
	minutes. Get medical attention promptly if symptoms occur after washing.
	RINSE IMMEDIATELY WITH PLENTY OF WATER REMOVE CONTAMINATED
Skin Contact	CLOTHING
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk
IIIgestion	instead of water if
	readily available. Keep affected person under observation. Do not induce
	vomiting. If vomiting
	occurs, the head should be kept low so that vomit does not enter the lungs.
	Get medical
	attention immediately. Show this Safety Data Sheet to the medical
	personnel.
4.2 Most important symptoms ar	ND EFFECTS, BOTH ACUTE AND DELAYED
Inhalation	GAS OR VAPOUR IN HIGH CONCENTRATIONS MAY IRRITATE THE RESPIRATORY
Eve contact	SYSTEM.
Eye contact	Irritating to eyes. Symptoms following overexposure may include the
Skin Contact	following: Redness. Pain.
Skiii Goillagt	REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.
Ingestion	GASTROINTESTINAL SYMPTOMS, INCLUDING UPSET STOMACH.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED	
Specific treatments Seek medical attention if irritation or symptoms	
	persist. Symptomatic treatment



### **SECTION 5 FIREFIGHTING MEASURES**

### 5.1. Extinguishing media

5 5		
	Suitable extinguishing media	Extinguish with the following media: Alcohol-resistant foam.
		Carbon dioxide (CO2). Dry chemicals, sand, dolomite etc. Do
		not use water, if avoidable.

### 5.2. Special hazards arising from the substance or mixture

Specific hazards	The product is flammable. Heating may generate flammable
	vapours. Thermal decomposition
	or combustion products may include the following substances:
	Toxic gases or vapours.
5.3. Advice for firefighters	
Special protective equipment for	Wear positive-pressure self-contained breathing apparatus (SCBA)
firefighters	and appropriate protective clothing.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	protective equipment and emergency procedures	
	Personal precautions Wear protective clothing as described in Section 8 of	
	this safety data sheet.	
6.2 Environmental precautions		
Environmental precautions	Spillages or uncontrolled discharges into watercourses must be reported	
	immediately to the Environmental Agency or other appropriate regulatory	
	body. Collect and place in suitable waste disposal containers and seal	
	securely. Label the containers containing waste and contaminated	
	materials and remove from the area as soon as possible.	
6.3. Methods and material for containment and cleaning up		
Methods for cleaning up.  Absorb in vermiculity, dry sand or earth and place into containers		

	<b>.</b> .
Methods for cleaning up	Absorb in vermiculite, dry sand or earth and place into containers. Flush
	contaminated area with plenty of water. Wash thoroughly after dealing
	with a spillage.

### 6.4. Reference to other sections

Reference to other sections	See section 3,8 & 13 for further information
-----------------------------	--



### **SECTION 7 HANDLING & STORAGE**

### 7.1 PRECAUTIONS FOR SAFE HANDLING

Usage precautions Keep away from heat, sparks and open flame. Do
not wear contact lenses. Avoid spilling.
Avoid contact with skin and eyes. Eye wash facilities and emergency
shower must be
available when handling this product. During application and drying,
solvent vapours will be
emitted.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

	Storage precautions Store in tightly closed, original container in a dry
	and cool place. Store under well-ventilated conditions at a temperature
	below 25°C. Storage class Flammable liquid storage.

### 7.3 SPECIFIC END USE(S)

Specific end use(s) The identified uses for this product are detailed in Section
1.2.

# SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters Occupational exposure limits

### **ETHANOL**

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL

WEL = Workplace Exposure Limit

### **METHANOL**

Long-term exposure limit (8-hour TWA): WEL 200 ppm 266 mg/m³ Short-term exposure limit (15-minute): WEL 250 ppm 333 mg/m³

# Ingredient comments WEL = Workplace Exposure Limits ETHANOL

# Workers - Inhalation; Long term systemic effects: 950 mg/m³ Workers - Inhalation; Short term local effects: 1900 mg/m³ Workers - Dermal; Long term systemic effects: 343 mg/kg/day General population - Inhalation; Long term systemic effects: 114 mg/m³ General population - Inhalation; Short term local effects: 950 mg/m³ General population - Dermal; Long term systemic effects: 206 mg/kg/day General population - Oral; Long term systemic effects: 87 mg/kg/day PNEC - Fresh water; 0.96 mg/l - marine water; 0.79 mg/l - Intermittent release; 2.75 mg/l - STP; 580 mg/l - Sediment (Freshwater); 3.6 mg/kg - Sediment (Marine water); 2.9 mg/kg



- Soil; 0.63 mg/kg	
- Soil; 0.63 mg/kg	

### **METHANOL**

DNEL	Workers - Inhalation; Long term systemic effects: 260 mg/m³ Workers -
	Inhalation; Short term systemic effects: 260 mg/m³ Workers -
	Inhalation; Long term local effects: 260 mg/m³
	Workers - Inhalation; Short term local effects: 260 mg/m³
	Workers - Dermal; Long term systemic effects: 40 mg/m³
	Workers - Dermal; Long term systemic effects: 40 mg/kg/day General
	population - Inhalation; Long term systemic effects: 50 mg/m³ General
	population - Inhalation; Short term systemic effects: 50 mg/m³ General
	population - Inhalation; Long term local effects: 50 mg/m³ General
	population - Inhalation; Short term local effects: 50 mg/m³ General
	population - Dermal; Long term systemic effects: 8 mg/kg/day General
	population - Dermal; Short term systemic effects: 8 mg/kg/day General
	population - Oral; Long term systemic effects: 8 mg/kg/day General
	population - Oral; Short term systemic effects: 8 mg/kg/day
DMEL	Workers - Dermal; Long term systemic effects: 40 mg/kg/day
PNEC	- Fresh water; 20.8 mg/l
	- marine water; 2.08 mg/l
	- Intermittent release; 1540 mg/l
	- STP; 100 mg/l
	- Sediment (Freshwater); 77 mg/kg
	- Sediment (Marine water); 7.7 mg/kg
	- Soil; 100 mg/kg

### 8.2. Exposure controls

B ( ):	
Protective equipment	Eye protection must be worn
Appropriate engineering controls	Not relevant.
Eye/face protection	Contact lenses should not be worn when working with this chemical.
	Personal protective equipment for eye and face protection should comply
	with European Standard EN166. The following protection should be worn:
	Chemical splash goggles.
Hand protection	Hand protection not required.
Other skin & body protection	Provide eyewash station.
Hygiene measures	Promptly remove non-impervious clothing that becomes contaminated.
	When using do not eat, drink or smoke.
CECTION O DUVOICAL O CHEMICA	N DDODEDTIES

### SECTION 9 PHYSICAL & CHEMICAL PROPERTIES

### 9.1 Information on basic physical & chemical properties

Appearance	Gel
Colour	Colourless
Odour	Slightly alcoholic
рН	6-8
Flash point	22C°C PMCC (Pensky-Martens closed cup).
Relative density	0.87 @ 20°C



Solubility	Soluble in water.
Viscosity	10,000 CP@ @ 20°C

### SECTION 10 STABILITY & REACTIVITY

### 10.1. Reactivity

Reactivity	No test data specifically related to reactivity available for this product or
	its ingredients.
10.2. Chemical stability	
Stability	No particular stability concerns.
10.3. Possibility of hazardous re	eactions
Possibility of hazardous reactions	None known.
10.4. Conditions to avoid	
Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid contact with the
	following materials:
	Acids. Oxidising agents.
10.5. Incompatible materials	
Materials to avoid	Keep away from oxidising materials, heat and flames.
10.6. Hazardous decomposition products	
Hazardous decomposition products	Oxides of carbon. Protection against nuisance dust must be used when
	the airborne concentration exceeds 10 mg/m3.

### **SECTION 11 TOXILOGICAL INFORMATION**

### 11.1 Information on taxological effects

Inhalation	Gas or vapour in high concentrations may irritate the respiratory system.  Symptoms following overexposure may include the following: Coughing.
Ingestion	Gastrointestinal symptoms, including upset stomach.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	Irritating to eyes. Symptoms following overexposure may include the
	following: Redness.
	Pain.

### SECTION 12 ECOLOGICAL INFORMATION

Other adverse effects

Ecotoxicity	The product is not expected to be hazardous to the environment.
12.1. Toxicity	
	The product is not believed to present a hazard due to its physical
	nature.
12.2. Persistence and degradability	
Persistence and degradability	The product is biodegradable.
12.3. Bio accumulative potential	
Bio accumulative potential	No data available on bioaccumulation.
12.4. Mobility in soil	
Mobility	The product is soluble in water.
12.5. Results of PBT and vPvB assessment	
Results of PBT and vPvB assessment	This product does not contain any substances classified as PBT or vPvB
12.6 Other adverse effects	

None known

### SECTION 13 DISPOSAL COSIDERATION

### 13.1 Waste treatment methods

General information	Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Disposal methods	Absorb in vermiculite, dry sand or earth and place into containers. Dispose of waste via a licensed waste disposal contractor. Containers should be thoroughly emptied before disposal because of the risk of an explosion.

### **SECTION 14 TRANSPORT INFORMATION**

### 14.1. UN number

UN No. (ADR/RID)	1993
UN No. (IMDG)	1993
UN No. (ICAO)	1993

### 14.2. UN proper shipping name

Proper shipping name (ADR/RID)	FLAMMABLE LIQUID, N.O.S.
Proper shipping name (IMDG	FLAMMABLE LIQUID, N.O.S.
Proper shipping name (ICAO)	FLAMMABLE LIQUID, N.O.S.
Proper shipping name (ADN)	FLAMMABLE LIQUID, N.O.S.

### 4.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID label	3
IMDG class	3
ICAO class/division	3
Transport labels	

### 14.4. Packing group

ADF	R/RID packing group	III
IMD	OG packing group	III
ICA	O packing group	III

### **SECTION 15 REGULATORY INFORMATION**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

ion carety, near and content of a content of the carety of	
National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI
	2009
	No. 716).
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of
	18 December 2006 concerning the Registration, Evaluation, Authorisation and



	Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations CHIP for everyone HSG228.

### 15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

### Section 16 OTHER INFORMATION

Revision date	07/03/2020
Revision	01
SDS Number	HSG01
Risk phases in full	R10 Flammable. R11 Highly flammable. R22 Harmful if swallowed. R36 Irritating to eyes. R38 Irritating to skin. R41 Risk of serious damage to eyes. R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed.
Hazard statements in full	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H319 Causes serious eye irritation.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.